

EZZ PARK



Technical Specification

COMTUSTEC INDIA (P) LTD

General Description

A fully automated intelligent solution for parking management. State-of-the-art features to address parking related problems. Scalable design to fit into any kind of parking structure.

Hardware Specification

General

Peak current	460mA
Sleep current	28.3µA
Operating Temperature	-20° to 54°C
Software upgrade	Wireless over the air software upgrade
Status indicator	Buzzer
Car parking Indication	Yes
BLE (Bluetooth Low Energy)	
Frequency	2.4GHZ
Transmission Power	0dB
Control Range	20 Meters
Battery	
Battery	D-Type Battery 6 Numbers
Backup	1 Year / 10 operations per day
Standby	> 5 Years

Mechanical Specifications

Size	48X24X41.5cm
Weight	6.6Kgs
Height (When Barrier is Close)	41.5cm
Height (When Barrier is Open)	6.5cm
Colour	Yellow with black
Material	Steel
	IP55/Shock Proof, Dust Proof and Water Spill/Splash Proof.
Lock:	Manual lock provided to lock the electronics section.

Hardware Accessory

Expansion screw	6 numbers
-----------------	-----------

Warranty

Warranty	1 Year (*Only Manufacturing defects)
----------	--------------------------------------

Applications

Parking area protection

Residential, Business centres.

Parking space reservation

Shopping Malls, Airports, Hospitals & Smart cities.